

# LFGD-SP Series

## 3"/4" Gimbal Spot Float Can-less Recessed Downlight with 5CCT Selector

Project Name:	Order Number:	Prepare by:	Note:	Date:	Type:

### GIMBAL SPOT FLOAT


The **LFGD-SP Series** Canless Spot Float Gimbal downlight is designed to highlight the architectural and artistic elements in your home. It features adjustment of 80-degree tilt, 360-degree rotation, fully dimmable and 95 CRI rating (color rendering index). With the canless design, it no longer requires a recessed housing for the installation, allows you to install it almost anywhere. These recessed down lights are also designed for use in new construction, remodel and retrofit installation without needing a housing or j-box.

Perfect use for residential housings, condominiums, the healthcare facility, shopping centers and hospitality industry.



- Select color temperature from
- 2700K **WARM WHITE**
  - 3000K **SOFT WHITE**
  - 3500K **NATURAL WHITE**
  - 4000K **COOL WHITE**
  - 5000K **DAYLIGHT**

### DIMENSION



MODEL#	MFGD036-SP	MFGD049-SP
<b>A</b>	1.22"	1.5"
<b>B</b>	3.78"	5"


Energy Star® and ETL certified. It can be used to comply with Title-24 and JA8 high efficacy light source requirements.

### TECHNICAL SUMMARY

MODEL #	LUMENS	WATTS	EFFICACY	CRI	VOLTAGE	BEAM °	CCT	PF	LIFE	OPERATING TEMP.
<b>LFGD036-SP-5CCT-WH</b>	<b>345</b>	<b>6W</b>	58 lm/W	90	<b>120V, 60 Hz</b>	60°	2700K/ 3000K/ 3500K/ 4000K/ 5000K	>0.9	50,000 hrs	-5°F ~ 104°F
<b>LFGD049-SP-5CCT-WH</b>	<b>540</b>	<b>9W</b>	60 lm/W							

### PART NUMBER ORDERING SUMMARY

**L F G D 04 9 - SP - 5CCT-WH**



# LFGD-SP Series

3"/4"

Gimbal Spot Float Can-less Recessed Downlight with 5CCT Selector

Project Name:	Order Number:	Prepare by:	Note:	Date:	Type:

## CONSTRUCTION

Unit includes spinning metal housing, LED array, heat sink, lens, and foam gasket with deep baffle white ring.

## OPTICS

- High quality PC lens
- Efficiency LED array
- Diffuse for uniform illumination

## DRIVER

- High efficiency integral 120V 60Hz constant current dimmable driver.
- Smooth flicker free deep dimming to 10%

## MOUNTING


- Can-less design, no can housing needed for the installation
- Pre-installed surface mounting bracket adapter
- Junction box included
- Ceiling mount, directly mount on drywall

## LISTING

ETL Listed, Energy Star Listed, Suitable for Wet Locations, Title 24 JA8-2022, RoHS, Air-Tite Certified

## WARRANTY

5 years manufacturer warranty, consult factory for more details. Terms and conditions may apply.



## 360° AND 80°

These recessed light can be rotated 360° and tilt up to 80°. Easy for you to adjust the angle and direction after the installation.

## COMPATIBLE PRODUCTS (SOLD SEPARATELY)



### LRSDMP-346

Mounting plate for 3"/4"/6" can-less downlight



### L3FTCABLE

**L10FTCABLE** 3ft/  
10ft Extension cord for  
can-less downlight

## RECOMMENDED DIMMERS

### LUTRON

- TGCL-153PH-WH
- DVCL-153PR
- P-PKG1W-WH-R
- CTCL-153PDH-WH

### LEVITON

- R00-RNL06-TW
- R50-IPL06-10M