

Project Name:

Order Number:


Prepare by:

Note:

Date:

Type:

DESCRIPTION



Compact Fire Resistance Design




Select color temperature from
 • 2700K **WARM WHITE**
 • 3000K **SOFT WHITE**
 • 3500K **NATURAL WHITE**
 • 4000K **COOL WHITE**
 • 5000K **DAYLIGHT**




Product Information

Model No.	Product Name	Lumens	Watts	Efficacy	CRI	VOLTAGE	DIMMING	CCT	LIFE	OPERATING TEMP.
LRFR615W-BA-5CCT	6" Fire Rated Canless Baffle	1240LM	18W	69lm/w	90	120-347V	0-10	5CCT	>50,000hrs	-4°F ~ 104°F
LRFR615W-FL-5CCT	6" Fire Rated Canless Flat	1240LM	18W	69lm/w	90	120-347V	0-10	5CCT	>50,000hrs	-4°F ~ 104°F
LRFR615W-SM-5CCT	6" Fire Rated Canless Smooth	1240LM	18W	69lm/w	90	120-347V	0-10	5CCT	>50,000hrs	-4°F ~ 104°F

DIMENSIONS



4inch



6inch

L R FR 6 18W - BA - 5CCT

ROUND Shape FR Fire Rated 6INCH Size 18W Wattage BA/SM/FL 5CCT 27K/30K/35K/40K/50K

Project Name:

Order Number:


Prepare by:

Note:

Date:


Type:

PHOTOMETRY



4"

LRFR410W-BA-5CCT
LRFR410W-FL-5CCT
LRFR410W-SM-5CCT



6"

LRFR615W-BA-5CCT
LRFR615W-FL-5CCT
LRFR615W-SM-5CCT

TECHNICAL SUMMARY

CONSTRUCTION

Select color temperature from 2700k warm white, 3000k soft white, 3500k natural white, 4000k cool white, or 5000k daylight for your environment.

OPTICS

- High quality PC lens
- Efficiency LED array
- Diffuse for uniform illumination

DRIVER

- High efficiency integral 120v 60hz constant current dimmable driver.
- Smooth flicker free deep dimming to 10%.

MOUNTING

- Can-less design, no can housing needed for the installation.
- Pre-installed torsion spring clips.
- Junction box included.
- Quick wiring, no wiring nuts and electrical tap needed for the installation.

LISTING

- ETL Listed, Energy Star Listed, Suitable for Wet Locations, Title 24 JA8-2022, RoHS, Air-Tite Certified.

WARRANTY

- 5 years manufacturer warranty, consult factory for more details.
- Terms and conditions may apply.

FIRE RATED

- Complies with UL 263, tested and certified for 2 hours.
- Double steel wall casing filled with ceramic. Fiber Insulation.

COMPATIBLE PRODUCTS (SOLD SEPARATELY)



LRSDMP-346 Mounting plate for 3"/4"/6" can-less downlight



LRSDMP-468 Mounting plate for 4"/6"/8" can-less downlight



L3FTCABLE / L10FTCABLE
3ft/ 10ft Extension cord for can-less downlight

RECOMMENDED DIMMERS

LUTRON

- TGCL-153PH-WH
- DVCL-153PR
- P-PKG1W-WH-R
- CTCL-153PDH-WH

LEVITON

- R00-RNL06-TW
- R50-IPL06-10M